



**aquanex<sup>®</sup>**

*Environmentally Sealed  
IP67 Micro USB Range*

**GCT**

[www.gct.co](http://www.gct.co)

# Vital Stats

Introducing the **aquanex**<sup>®</sup> range from **GCT**. Micro USB connectors with an **IP67 rating** for protection against **dust and liquid ingress** (up to a depth of 1 meter)

A silicone seal is moulded to the exact connector profile to ensure reliability against the flange, creating an optimal seal. The stainless steel shell is made using an innovative **metal injection moulding** (MIM) manufacturing process. This one-piece shell construction adds integrity.

Water & Dust Proof

**IP67**

Injection Molded Shell

**Stainless Steel**

Operating Temp.

**-30 to +85°C**

Mating Cycles

**10,000**

Specification

**USB 2.0**

[gct.co/waterproof-connectors](https://gct.co/waterproof-connectors)

# aquanex® Range



## USB3500 - Mid PCB Mount

- IP67 Rated, USB 2.0 Micro Type B Horizontal Receptacle
- Single-piece injection molded stainless steel shell
- 1.425mm profile above PCB, Mid mount, Hybrid PCB mount
- 4 Through-hole shell stakes, 5 SMT solder tails



## USB3505 - Top PCB Mount

- IP67 Rated, 5 Pin USB 2.0 Micro Type B Horizontal Receptacle
- Single-piece injection molded stainless steel shell
- 2.95mm profile above PCB, Top mount, Hybrid PCB mount
- 4 Through-hole shell stakes, 5 SMT solder tails




## USB3510 - Vertical **Coming Soon**

- IP67 Rated, 5 Pin USB 2.0 Micro Type B Vertical Receptacle
- Single-piece injection molded stainless steel shell
- 5.20mm profile above PCB, Top mount, Surface mount
- 4 Through-hole shell stakes, 5 SMT solder tails

# USB3500 Key Specs


The first in the **aquanex®** range - **USB3500** - is a horizontal mid-plane top-mount micro USB with a profile above the PCB of just **1.425mm** and a total main body height of 2.9mm, allowing it to squeeze into the tightest of designs. 4 mounting posts provide secure attachment to the PCB - no screws or fixing needed.



- Nickel plated shell
- Conforms to USB 2.0 specification
- Power Rating: 1.0A Signal pins 2, 3 & 4
- Power Rating: 1.8A Power pins 1 & 5
- Supplied in Tape & Reel packaging

[gct.co/connector/usb3500](http://gct.co/connector/usb3500)

# USB3500 Key Dimensions



- 1 **aquanex**® injection molded stainless steel shell
- 2 Silicone gasket for IP67 protection
- 3 4 stainless steel mid-mount locating pegs
- 4 1.425mm low-profile mid-mount design
- 5 30μ" gold-plated contacts
- 6 Micro USB 2.0 Type B interface



# USB3505 Key Specs


The second in the **aquanex®** range - **USB3505** - is a horizontal top-mount micro USB with a profile above the PCB of just **2.95mm** and a total main body depth of 5.3mm, allowing it to squeeze into the tightest of designs. 4 mounting posts provide secure attachment to the PCB - no screws or fixing needed.



- Nickel plated shell
- Conforms to USB 2.0 specification
- Power Rating: 1.0A Signal pins 2, 3 & 4
- Power Rating: 1.8A Power pins 1 & 5
- Supplied in Tape & Reel packaging

[gct.co/connector/usb3505](http://gct.co/connector/usb3505)

# USB3505 Key Dimensions



- 1 **aquanex**® injection molded stainless steel shell
- 2 Silicone gasket for IP67 protection
- 3 4 stainless steel bottom-mount locating pegs
- 4 1.425mm low-profile mid-mount design
- 5 30μ" gold-plated contacts
- 6 Micro USB 2.0 Type B interface

# Website



## Technical Documentation

Detailed Product Drawings | Specification & Testing Documents



## Instant 3D CAD Model & PCB Footprint Downloads

Configure & download any GCT part in seconds | Universal & software-specific file types



## Quick Quoting & Express Sampling

Online Part Number Builder | Live Chat with our Experts | 72 hour Sampling on Select Ranges



## Custom Connector & Cable Assembly Capabilities

Bespoke Designs from Idea to Reality | Overmolded, IDC & Crimp Cable Assembly Options



## Local Support with a Global Footprint

GCT Locations in Europe, the Americas, and Asia | Worldwide Distribution Partners

 **London UK**  
+44 01707 321122  
sales@gct-europe.com

 **Boston MA, USA**  
+1 978 208 1618  
sales@gct-americas.com

 **Hong Kong HK**  
+852 2578 9030  
sales@gct-apac.com

 **Düsseldorf DE**  
+49 2166 555 1345  
salesde@gct-europe.com

 **San Jose CA, USA**  
+1 650 448 9660  
sales@gct-americas.com

 **Singapore SG**  
+65 8322 2263  
sales@gct-apac.com

[www.gct.co](http://www.gct.co)